



TECHNICAL SPECIFICATIONSGASTONE pick-up longGASTONE pick-up shortGECO / GRIFO shuttleHomologationN1FrameAluminium EN AW-5754 H111RangeUp to 130 km. per day* (vehicle consumption certified by ECE101 test)Max. payloadUp to 1.250 kg.Seats2GASTONE6/7 (8 - private areas)Wheelchair//GECOTyres145 R 13 C (165 R 13 or M+S - optional)Max. speed40 km/hLoading bed1.100 X 2.400 mm.1.100 x 1.800 mm.//Electronic control driveCurtis inverter with vector algorithmEngine brake with energy recoveryYesEFS (Electric power steering)OptionalBatteriesLead sealed GEL /AGM - no refilling neededEnergy accumulation16,2 kWh (24,1 kWh - optional)Ithium batteries12.8 kWh / 15.3 kWh - on requestQuick battery replacementIn less than 5 minutes with transpalletVith security sensor450 kg. homologation (3.000 kg. private area)Width, mm1.2001.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mmHeight, mm1.9402.270Warranty24 months, 10 years on the chassis				
HomologationN1FrameAluminium EN AW-5754 H111RangeUp to 130 km. per day* (vehicle consumption certified by ECE101 test)Max. payloadUp to 1.250 kg.Luggage 260/380 kg.6/7 (8 - private areas)Seats26/7 (8 - private areas)Wheelchair//GECOTyres145 R 13 C (165 R 13 or M+S - optional)Max. speed40 km/hLoading bed1.100 X 2.400 mm.1.100 X 1.800 mm.Max. speed1.100 X 2.400 mm.1.000 x 1.800 mm.Electric motor AC, three-phase10 kW - peak 15 kWElectronic control driveCurtis inverter with vector algorithmEngine brake with energy recoveryYesEPS (Electric power steering)OptionalBatteriesLead sealed GEL/AGM - no refilling neededEnergy accumulation16,2 kWh (24,1 kWh - optional)16,2 kWhLithium batteries12.8 kWh / 15.3 kWh - on requestQuick battery replacementIn less than 5 minutes with transpallet//Mit security sensorElectric heater / With security sensor//Electric heater / WebastoWith thermostat / optional1.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270				-
FrameAluminium EN AW-5754 H111RangeUp to 130 km. per day* (vehicle consumption certified by ECE101 test)Max. payloadUp to 1.250 kg.Luggage 260/380 kg.6/7 (8 - private areas)Wheelchair//GECOTyres145 R 13 C (165 R 13 or M+S - optional)Max. speed40 km/hLoading bed1.100 X 2.400 mm.1.100 x 1.800 mm.//Electric motor AC, three-phase10 kW - peak 15 kWElectronic control driveCurtis inverter with vector algorithmEngine brake with energy recoveryYesEPS (Electric power steering)OptionalBatteriesLead sealed GEL /AGM - no refilling neededEnergy accumulation16,2 kWh (24,1 kWh - optional)16,2 kWhLithium batteries12.8 kWh / 15.3 kWh - on requestQuick battery replacementIn less than 5 minutes with transpallet//Mattery chargerOn board. High frequency with PECDriver seatWith thermostat / optionalWebasto450 kg. homologation (3.000 kg. private area)//Width, mm1.2001.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270	Homologation	pick up tong		
RangeUp to 130 km. per day* (vehicle consumption certified by ECE101 test)Max. payloadUp to 1.250 kg.Luggage 260/380 kg.Seats26/7 (8 - private areas)Wheelchair//GECOTyres145 R 13 C (165 R 13 or M+5 - optional)Max. speed40 km/hLoading bed1.100 X 2.400 mm.1.100 x 1.800 mm.Max. speed40 km/hElectric motor AC, three-phase10 kW - peak 15 kWElectronic control driveCurtis inverter with vector algorithmEngine brake with energy recoveryYesEPS (Electric power steering)OptionalBatteriesLead sealed GEL /AGM - no refilling neededEnergy accumulation16,2 kWh (24,1 kWh - optional)16,2 kWhLithium batteries12.8 kWh / 15.3 kWh - on request//Quick battery replacementIn less than 5 minutes with transpallet//Driver seatWith security sensor//Electric heater / WebastoWith thermostat / optionalHeight, mm3.8903.2304.000/3.982Height, mm1.9402.270				
Max. payloadUp to 1.250 kg.260/380 kg.Seats26/7 (8 - private areas)Wheelchair//GECOTyres145 R 13 C (165 R 13 or M+S - optional)Max. speed40 km/hLoading bed1.100 X 2.400 mm.1.100 x 1.800 mm.Loading bed1.100 X 2.400 mm.1.100 x 1.800 mm.Electric motor AC, three-phase10 kW - peak 15 kWElectronic control driveCurtis inverter with vector algorithmEngine brake with energy recoveryYesEPS (Electric power steering)OptionalBatteriesLead sealed GEL /AGM - no refilling neededEnergy accumulation16,2 kWh (24,1 kWh - optional)16,2 kWhLithium batteries12.8 kWh / 15.3 kWh - on requestQuick battery replacementIn less than 5 minutes with transpallet//Battery chargerOn board. High frequency with PFCDriver seatWith security sensorElectric heater / WebastoWith thermostat / optionalTowbar450 kg. homologation (3.000 kg. private area)//Width, mm1.2001.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270		Up to 130 km. per day*		
Seats2private areas)Wheelchair//GECOTyres145 R 13 C (165 R 13 or M+S - optional)Max. speed40 km/hLoading bed1.100 X 2.400 mm.1.100 x 1.800 mm.Max. speed1.100 X 2.400 mm.1.100 x 1.800 mm.Electric motor AC, three-phase10 kW - peak 15 kWElectronic control driveCurtis inverter with vector algorithmEngine brake with energy recoveryYesEPS (Electric power steering)OptionalBatteriesLead sealed GEL /AGM - no refilling neededEnergy accumulation16,2 kWh (24,1 kWh - optional)16,2 kWh (24,1 kWh - optional)16,2 kWhLithium batteries12.8 kWh / 15.3 kWh - on requestQuick battery replacementIn less than 5 minutes with transpalletMith security sensorVith security sensorElectric heater / WebastoWith thermostat / optionalTowbar450 kg. homologation (3.000 kg. private area)Width, mm1.2001.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270	Max. payload	Up to 1.250 kg.		
Tyres145 R 13 C (165 R 13 or M+S - optional)Max. speed40 km/hLoading bed1.100 X 2.400 mm.1.100 X 1.800 mm.//Electric motor AC, three-phase10 kW - peak 15 kW//Electronic control driveCurtis inverter with vector algorithm//Engine brake with energy recoveryYes//EPS (Electric power steering)Optional16,2 kWhBatteriesLead sealed GEL /AGM - no refilling needed//Energy accumulation16,2 kWh (24,1 kWh - optional)16,2 kWhLithium batteries12.8 kWh / 15.3 kWh - on request//Quick battery replacementIn less than 5 minutes with transpallet//Battery chargerOn board. High frequency with PFCDriver seatWith security sensor//Electric heater / WebastoWith thermostat / optional//Width, mm1.2001.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270	Seats	2		, ,
Max. speed40 km/hLoading bed1.100 X 2.400 mm.1.100 x 1.800 mm.I.100 X 1.800 three-phase1.100 X 1.800 mm.Electroic control driveCurtis inverter with vector algorithmEngine brake with energy recoveryYesEPS (Electric power steering)OptionalBatteriesLead sealed GEL /AGM - no refilling neededEnergy accumulation16,2 kWh (24,1 kWh - optional)Lithium batteries12.8 kWh / 15.3 kWh - on requestQuick battery replacementIn less than 5 minutes with transpalletPriver seatWith security sensorElectric heater / WebastoWith thermostat / optionalTowbar450 kg. homologation (3.000 kg. private area)Vidth, mm1.2001.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270	Wheelchair	//		GECO
Loading bed1.100 X 2.400 mm.1.100 x 1.800 mm.//Electric motor AC, three-phase10 kW - peak 15 kW//Electronic control driveCurtis inverter with vector algorithmEngine brake with energy recoveryYesFPS (Electric power steering)OptionalBatteriesLead sealed GEL /AGM - no refilling neededEnergy accumulation16,2 kWh (24,1 kWh - optional)16,2 kWh (24,1 kWh - optional)16,2 kWhLithium batteries12.8 kWh / 15.3 kWh - on requestQuick battery replacementIn less than 5 minutes with transpallet//Mith security sensorElectric heater / WebastoWith thermostat / optionalTowbar450 kg. homologation (3.000 kg. private area)//1.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270	Tyres	145 R 13 C (165 R 13 or M+S - optional)		tional)
Loading bed1.100 X 2.400 mm.mm.//Electric motor AC, three-phase10 kW - peak 15 kWElectronic control driveCurtis inverter with vector algorithmEngine brake with energy recoveryYesEPS (Electric power steering)OptionalBatteriesLead sealed GEL /AGM - no refilling neededEnergy accumulation16,2 kWh (24,1 kWh - optional)16,2 kWh (24,1 kWh - optional)16,2 kWhLithium batteries12.8 kWh / 15.3 kWh - on requestQuick battery replacementIn less than 5 minutes with transpalletV/Battery chargerOn board. High frequency with PFCDriver seatWith security sensorElectric heater / Webasto450 kg. homologation (3.000 kg. private area)Towbar450 kg. homologation (3.000 kg. private area)Loading bed1.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270	Max. speed	40 km/h		
10 kW - peak 15 kWElectronic control driveCurtis inverter with vector algorithmEngine brake with energy recoveryYesEPS (Electric power steering)OptionalBatteriesLead sealed GEL /AGM - no refilling neededEnergy accumulation16,2 kWh (24,1 kWh - optional)16,2 kWhLithium batteries12.8 kWh / 15.3 kWh - on request//Quick battery replacementIn less than 5 minutes with transpallet//Battery chargerOn board. High frequency with PFCDriver seatWith security sensorElectric heater / WebastoWith thermostat / optionalTowbar450 kg. homologation (3.000 kg. private area)//Width, mm1.2001.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270	Loading bed	1.100 X 2.400 mm.		//
Engine brake with energy recoveryYesEPS [Electric power steering)OptionalBatteriesLead sealed GEL /AGM - no refilling neededEnergy accumulation16,2 kWh (24,1 kWh - optional)16,2 kWh (24,1 kWh - optional)16,2 kWhLithium batteries12.8 kWh / 15.3 kWh - on requestQuick battery replacementIn less than 5 minutes with transpalletMith security sensor//Electric heater / WebastoWith security sensorElectric heater / Webasto450 kg. homologation (3.000 kg. private area)Towbar450 kg. homologation (3.000 kg. private area)Midth, mm1.2001.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270		10 kW - <b>peak 15 kW</b>		
energy recoveryYesEPS (Electric power steering)OptionalBatteriesLead sealed GEL /AGM – no refilling neededEnergy accumulation16,2 kWh (24,1 kWh – optional)16,2 kWhLithium batteries12.8 kWh / 15.3 kWh - on requestQuick battery replacementIn less than 5 minutes with transpallet//Battery chargerOn board. High frequency with PFCDriver seatWith security sensorElectric heater / WebastoWith thermostat / optionalTowbar450 kg. homologation (3.000 kg. private area)//Width, mm1.2001.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270	Electronic control drive	Curtis inverter with vector algorithm		
Steering)OptionalBatteriesLead sealed GEL /AGM - no refilling neededEnergy accumulation16,2 kWh (24,1 kWh - optional)16,2 kWhLithium batteries12.8 kWh / 15.3 kWh - on requestQuick battery replacementIn less than 5 minutes with transpallet//Battery chargerOn board. High frequency with PFCDriver seatWith security sensorElectric heater / WebastoWith thermostat / optionalTowbar450 kg. homologation (3.000 kg. private area)//Width, mm1.2001.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270	0	Yes		
Energy accumulation16,2 kWh (24,1 kWh - optional)16,2 kWhLithium batteries12.8 kWh / 15.3 kWh - on requestQuick battery replacementIn less than 5 minutes with transpallet//Battery chargerOn board. High frequency with PFCDriver seatWith security sensorElectric heater / WebastoWith thermostat / optionalTowbar450 kg. homologation (3.000 kg. private area)//Width, mm1.2001.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270		Optional		
Lithium batteries   12.8 kWh / 15.3 kWh - on request     Quick battery replacement   In less than 5 minutes with transpallet   //     Battery charger   On board. High frequency with PFC     Driver seat   With security sensor     Electric heater / Webasto   With thermostat / optional     Towbar   450 kg. homologation (3.000 kg. private area)   //     Width, mm   1.200   1.200/1.360     Lenght, mm   3.890   3.230   4.000/3.982     Height, mm   1.940   2.270	Batteries	Lead sealed GEL /AGM – no refilling needed		
Quick battery replacementIn less than 5 minutes with transpallet//Battery chargerOn board. High frequency with PFCDriver seatWith security sensorElectric heater / WebastoWith thermostat / optionalTowbar450 kg. homologation (3.000 kg. private area)//Width, mm1.2001.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270	Energy accumulation			16,2 kWh
replacementIn less than 5 minutes with transpallet//Battery chargerOn board. High frequency with PFCDriver seatWith security sensorElectric heater / WebastoWith thermostat / optionalTowbar450 kg. homologation (3.000 kg. private area)//Width, mm1.2001.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270	Lithium batteries	12.8 kWh / 15.3 kWh - on request		
Driver seat With security sensor   Electric heater / Webasto With thermostat / optional   Towbar 450 kg. homologation (3.000 kg. private area) //   Width, mm 1.200 1.200/1.360   Lenght, mm 3.890 3.230 4.000/3.982   Height, mm 1.940 2.270		In less than 5 minutes with transpallet		//
Electric heater / Webasto With thermostat / optional   Towbar 450 kg. homologation (3.000 kg. private area) //   Width, mm 1.200 1.200/1.360   Lenght, mm 3.890 3.230 4.000/3.982   Height, mm 1.940 2.270	Battery charger	On board. High frequency with PFC		
WebastoWith thermostat / optionalTowbar450 kg. homologation (3.000 kg. private area)//Width, mm1.2001.200/1.360Lenght, mm3.8903.2304.000/3.982Height, mm1.9402.270	Driver seat	With security sensor		
I owbar     area)     //       Width, mm     1.200     1.200/1.360       Lenght, mm     3.890     3.230     4.000/3.982       Height, mm     1.940     2.270	-	With thermostat / optional		
Lenght, mm     3.890     3.230     4.000/3.982       Height, mm     1.940     2.270	Towbar			//
Height, mm     1.940     2.270	Width, mm	1.200		1.200/1.360
	Lenght, mm	3.890	3.230	4.000/3.982
Warranty     24 months, 10 years on the chassis	Height, mm	1.940		2.270
	Warranty	24 months, 10 years on the chassis		

















**ESAGONO ENERGIA SRL - Via Puecher, 9** 20060 Pozzuolo Martesana (MI) – Italy Tel. +39 02 95359270 - Fax. +39 02 95359114 info@esagonoenergia.it - www.esagonoenergia.com











and 100%











Our company, located in Milan – Italy (since 1985) designs and produces totally electrical, short-range commercial vehicles for the transportation of goods and people. They are zero-emissions and low noise vehicles and allow savings in maintenance costs.

### We produce:

- GASTONE PICK-UP, for transportation of goods, available in long and short versions with more than 20 configurations;
- GECO & GRIFO SHUTTLES, for transportation of up to 7 people, wheelchair is possible;
- GAGLIOFFO, for use in private areas, includes a special configuration for disabled persons transportation, for railways.

## OUR "PLUS":

- ✓ Entirely Made in Italy
- ✓ N1 EU homologation
- ✓ Aluminium frame
- ✓ Big payload: up to 1.250 Kg. (2755 lb.)
- ✓ Long range: up to 130 Km./day (80 miles)\*, certified ECE101

# MORE THAN 20 PICK-UP CONFIGURATIONS, AMONG THEM:

- fitted with sides
- tipper
- close van
- rack & canvas
- isothermal or cooling van
- waste tipping unit
- washer & irrigation unit
- vacuum aspiration cleaner and other special configurations on request.



\*Depending on battery used. The real distance per charge of the battery depends on several factors including the total load transported, the average speed, path, driving behavior, the ambient temperature, the power consumption of any configuration, etc.








Electric pick-up Gastone is a versatile and functional vehicle that offers new solutions to sustainable mobility within the restricted traffic zones, urban centers, logistics centers, green areas.

Our electric pick-ups and more than 20 configurations are entirely Made in Italy, they are environmentally friendly and are a valuable ally for your work



#### STANDARD EQUIPMENT

#### Structure

- Chassis in aluminium, 10 years guaranteed.
- Shockproof chassis structure.
- Materials recyclable over 97%, according to European Directive 2005/64/CE.

### **Electric features**

- Energy recovery.
- Rear-wheel drive.
- 10 kW high efficiency AC three-phase motor (15kW peak).
- Curtis motor controller.
- Nominal voltage 72V.
- Battery in GEL/AGM 72V refilling free and fast replacement. Lithium battery is available.
- Onboard automatic battery charger.

#### **Mechanical parts**

- Rack and pinion steering.
- Front wheels: suspentions independent wheel Mac Pherson with helical springs and hydraulic shock absorber.
- Rear-wheels: leaf-spring with hydraulic shock-absorber.
- Brakes system: front dual circuit disk brakes with brakeforce distribution, rear drum brakes.
- Battery compartment protected from atmospheric agents.
- Electric, electronic and mechanical components protected against ice, salt and impacts.
- Tyres 145 R 13 (165 R 13 or M+S -are available).

### **Comfort and Security**

- Roomy and ergonomic cabin.
- Padded adjustable seats with headrests.
- Three-point safety belts.
- Adjustable steering wheel.
- Double-speed electric wiper.
- Display with indications of speed, battery status, hour-counter and anomalies.
- Electric heater with thermostat.
- Driver seat with security sensor.
- Additional socket 12V.

### Performance

.

- Range: up to 130 km\*, certified ECE101.
- Max speed: 40 Km/h.
- Mileage cost: 1,50 € / 100 km (depending on the energy supplier).
- Max slope: 15% full loaded (19% option).

#### Homologation

• N1 EU Truck (driving licence class B).



k canvas